

Mosaic Color Coating – P91 Series

www.proformax.com

1-800-765-6699

Finish Description:

Mosaic Color's distinctive multi-color tactile finish provides a unique varying depth appearance that ensures durability and cosmetic appeal. It hides stains and makes uneven surfaces look their level best.

Recommended Use:

All Properly Prepared Interior Walls, including Masonry, and Metal Surfaces.

Surface Preparation:

Surfaces should be clean, dry and free of dust, grease, wax or other contaminants. Gloss surfaces need to be deglossed or scuff sanded prior to priming and finish application. Stains should be spot primed with a quality Stain Blocking primer before general priming.

Application:

Spray only. Mosaic should be applied using airless spray equipment only, and according to manufacturer's published installation guidelines. Consult application guide for techniques and tips.

Clean-up:

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Thoroughly flush spray equipment with clean warm water.

Touch-up:

If a patching compound has been used spot prime with Ceramic Based Undercoater – P62 Series. Apply Mosaic following manufacturer's application guidelines. Softly blend spray pattern from center towards outer perimeter. In some cases small handheld airless spray devices may work. Call ICP Building Solutions Group at 1-800-765-6699 for more information.

PRECAUTIONS

Do not add solvents, oils or colors in oil, or mix with other paint types. Low temperature, high humidity, or inadequate ventilation will slow drying times. Keep from freezing. **Keep out of reach of children. Do not take internally. Close container after each use. Refer to Safety Data Sheet for additional health and safety information.**

TECHNICAL DATA**Finish Appearance:** Textured Multicolor**Colors Available:** 21 Colors**Scrub Rating:** 3,200**Resin Type:** 100% Acrylic**Specular Gloss:** Maximum of 10 @ 60° Angle**Volume Solids:** 29-32%**Weight Solids:** 38-42%**Wet Film Thickness:** 8-10 mils**Dry Film Thickness:** 2.5 - 3.0 Mil**Max VOC:** 50 g/l**Flash Point:** Non-Combustible**Coverage Rate:** Up to 160 sq. ft. per gallon (depending upon color, pattern size, surface porosity, surface texture and method of application.)**Drying Times****To Touch:** 2-4 Hours**To Recoat:** 2-4 Hours**Full Cure:** 7-10 Days**Surface Temperature At Application****Min:** 50°F **Max:** 85°F

Relative Humidity: < 50%

Tools and Equipment

Spray: Spray only. Mosaic Color Coating should be sprayed using airless spray equipment according to manufacturer's published installation guide. Consult application guide for techniques and tips.

ARCHITECTURAL SPECIFICATIONS**Properly Prepared Interior Walls:**

Primer Coat - 1 or 2 coats of Ceramic Based Undercoater – P62 Series.

Initial Coat - Mosaic Color Coating – P91 Series

Final Coat - Mosaic Color Coating – P91 Series

Ceramic base coat P62 Series must be uniform in appearance to achieve desired finish look.