

Decorative Surface Defender – P2 Series

www.proformax.com

1-800-765-6699

Finish Description:

Interior Decorative Surface Defender is a high performing catalyzed clear that encapsulates a decorative fleck very hard, impervious film and creates a continuous barrier that protects the surface.

Recommended Use:

Use over existing 100% acrylic water-based finishes and Proformax solid coatings. Surface must clean. May require more than one coat over some finishes. For interior use only.

Surface Preparation:

All Proformax coatings must be fully dry and must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination, prior to application of Surface Defender Clear

Application:

Surface Defender must have Masterlink additive added prior to use. Add Masterlink bottle to each gallon or 5 Gallon container, and slowly stir in ensuring no bubbles are created. **Do not use mechanical shaker or drill attachment.**

Clean-up:

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try lacquer thinner, followed by warm soapy water and a clear water rinse.

Touch-up:

Call ICP Building Solutions Group at 1-800-765-6699 for more information.

TECHNICAL DATA

Finish Appearance: Clear with decorative fleck**Scrub Rating:** 6,500 scrubs**Resin Type:** Acrylic Polyurethane**Specular Gloss:** Flat - 0 Satin - 45 Gloss - 75**Volume Solids:** 31%**Weight Solids:** 33%**Wet Film Thickness:** 4 mils**Dry Film Thickness:** 2 mils**Viscosity @ 77° F:** 69**Max VOC:** 150 g/l**Flash Point:** Non Combustible**Coverage Rate:** Coverage rates will vary on application technique**Drying Times****To Touch:** 20 minutes**To Recoat:** 1 hour under normal drying conditions**Surface Temperature At Application****Min:** 50° F **Max:** 80° F**Relative Humidity:** < 50%**Tools and Equipment****Spray:** Conventional or HVLP**Note:** please refer to Application Guide

ARCHITECTURAL SPECIFICATIONS

Painted surfaces: Apply 1 or 2 coats of P1 Interior Surface Defender over 100% Acrylic Paints. 1 coat of Decorative Surface Defender – P2 Series**Proformax Finishes:**

1 coat of Decorative Surface Defender – P2 Series

Areas of Extreme Wear & Washing:

Apply an additional protective layer of Interior Surface Defender – P1 Series

PRECAUTIONS

Use only with adequate ventilation. Close container after each use. **KEEP OUT OF REACH OF CHILDREN.** Refer to Safety Data Sheet for additional health and safety information. **Keep From Freezing.**